



Flood risk assessment in a Spanish Mediterranean catchment

S. Salazar (1), F. Francés (1), R. García-Bartual (1), E. Ortiz (2), J.C. Múnera (1), and J.J. Vélez (3)

(1) Technical University of Valencia, Hydraulic and Hydrology Research Group, Hydraulic Engineering and Environmental, Valencia, Spain (sersaga@doctor.upv.es), (2) HidroGaia, S.L., Avenida Juan de la Cierva, 27, 46980 Valencia, Spain, (3) Universidad Nacional de Colombia, sede Manizales, Dep. Ingeniería Civil, Idea A.A.127, Colombia

This paper describes a multidisciplinary approach for the risk assessment and its application to analysing the effects of extreme flood events on the Mediterranean catchment called “Rambla del Poyo” in Valencia (Spain). This catchment located in the East coast of Spain has an area of 380 km² and is clearly open to the Mediterranean Mesoscale Convective Storms. The climate is semiarid, and the flow regime is typically ephemeral, but with highly frequent flash floods, with peak flows in the order of 500 m³/s. Recently, in 2000 and 2002 the area was severe flooded. The flood prone area is located in the lower part of the basin, with an important concentration of different urban centers and industrial and commercial areas (including part of the Valencia International Airport). For this reason, the analysis of damages of residential, industrial and commercial urbanized areas is essential for the prevention of damages with a proper flood risk management.

The approach is based on three main steps. The first step entails a detailed hydrological analysis (parameter estimation, calibration-validation and simulations) using a distributed rainfall-runoff model called TETIS. In the case study, on one hand, high temporal resolutions rain gauge data are scarce, because of this, in addition to a small number of historic events, 100 synthetic rainstorms were generated using the multidimensional stochastic model called RAINGEN, which adequately represents the main structural properties typical of intense convective storms, including occurrence of raincells in space and time and the generated intensities. An equivalent daily maximum precipitation Pd was estimated for each synthetic event, thus allowing a return period assignment using the known statistical distribution of Pd in the region. On the other hand, the initial soil moisture condition can have a strong influence in the runoff production, for this reason, long term daily simulation has been done in order to assess the probability distribution of the initial situation before the extreme flood events (dry and wet conditions). For all combinations of precipitation inputs and initial conditions, 200 hydrological simulations has been done in order to obtain the input hydrographs for the hydraulic model. Finally in this step, a frequency analysis to obtain the non-exceedence probability of the peak discharges has been developed using the annual maximum daily precipitation and the initial soil moisture condition with this expression:

$$F_X(x) = \int_{-\infty}^{\infty} F_{X|r}(x|r) \cdot f_R(r) \cdot dr$$

where: X= random variable of interest (peak discharge), R= annual maximum daily precipitation, $f_R(r)$ = probability density function of R, $F_{X|r}(x/r)$ = conditional density function of X given r obtained from simulations.

The main objective of second step is flood hazard estimation, which, the hydraulic modelling has been developed using the coupled computing version of Sobek 1D/2D. In this task, the treatment of DEM calculation can be a key task depending on the scale of work. The introduction of buildings, walls, the opening of drainage works... improving the quality of results in areas with high anthropogenic influence; in our case has been made 6 simulations with 3 different resolutions, after all, the model has been done with a model one-dimensional (1D), logging throughout the stretch to two-dimensional (2D) grid with the parent of 30x30 metres, except for its passage through the urban, commercial and industrial land uses in the flood prone area where it connects with the child grid of 10x10 metres. Unfortunately, for reasons of computer time, the hydraulic model has not been run for the 200 available events. However, 20 events have been carefully select trying to cover the best probabilistic interest spectrum for this study (from two to one thousand years of return period). From the 20 selected flooding maps it has been developed a GIS

computational tool for calculating a regression between the independent variable (maximum water depth) and the dependent variable return period transformed into natural logarithm. Using this methodology have been generated the hazard maps for the return periods of interest.

Finally, the third step concerns to the flood risk, which was defined as probabilistic integral of the combination of flood hazard and land use vulnerability:

$$R = \int_0^{\infty} V(h) \cdot f_H(h) \cdot dh$$

Where: R is the flood risk, V(h) is the land use vulnerability, h is the flood magnitude and $f_H(h)$ is its probability density function. The land use vulnerability is expressed in terms of stage-damage functions for urban, commercial and industrial land uses. Both, flood hazard and land use vulnerability are defined in terms of magnitude (water depth). This integral has been solved in discrete form using a GIS tools. The flood risk assessment by a resolution of 10 meters in size cell in the flood prone area of the “Rambla del Poyo” has been done. With this useful methodology, we believe that a complete flood risk analysis is needed in order to objectively compare different future scenarios that can affect either the flood hazard and/or the vulnerability in the flood prone area.